



SAFETY DATA SHEET

HOUGHTON®

Revision Date 07-21-2015

Version 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code(s) 64089351-M
Product Name STEELSHIELD 6299

Recommended Use Rust Preventative
Uses advised against Any other purpose.

Manufacturer, Importer, Supplier

Houghton International Inc.
Madison & Van Buren Aves.
Valley Forge, PA 19482
Telephone: 610-666-4000 FAX: 610-666-1376
Website: www.houghtonintl.com
Customer Service: 888-459-9844

Houghton Canada
915 Meyerside Drive
Mississauga
ON
L5T 1R8

Houghton Mexico S.A. de C.V.
Efraín Gonzalez Luna, 2007 Depto19
Col. Americana, Guadalajara,
Jalisco CP. 44160,
Mexico
Phone: +52-333-615-9331

Emergency telephone number

3E Company 1-866-519-4752 (USA, Canada, Mexico)
Company Access Code: 333938

SECTION 2: HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1

Label elements

Signal word
DANGER

Hazard statements

Causes serious eye irritation
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways



Precautionary Statements**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Health Not Applicable.

Physical Not Applicable.

Other Information

Prolonged skin contact may defat the skin and produce dermatitis

Repeated exposure may cause skin dryness or cracking

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients.

Chemical name	CAS No	Weight-%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	60% - 100%
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	-	2.5% - 10%
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	2.5% - 10%
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts (TSCA Inventory - CAS# 148520-82-5)	68411-30-3	1% - 2.5%
Stoddard solvent	8052-41-3	1% - 2.5%
2,6-Di-tert-butyl-p-cresol	128-37-0	0% - 1%

The exact percentage (concentration) of composition has been withheld as a trade secret.

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. See Section 15 for additional information on base oils.

SECTION 4: FIRST AID MEASURES**Description of first-aid measures****General advice**

Immediate medical attention is required. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

Inhalation

Get medical attention immediately if symptoms occur. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Potential for aspiration if

	swallowed.
Skin contact	If symptoms persist, call a physician. Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use.
Eye contact	Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not rub affected area. Seek immediate medical attention/advice.
Ingestion	Do not induce vomiting without medical advice. Clean mouth with water and afterwards drink plenty of water. Call a POISON CENTER or doctor/physician if exposed or you feel unwell. Aspiration hazard if swallowed - can enter lungs and cause damage.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Main Symptoms May be fatal if swallowed and enters airways, Eye damage/irritation

Indication of immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES**Extinguishing media****Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

Special hazards arising from the substance or mixture**Special Hazard**

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). This material creates a fire hazard because it floats on water. Thermal decomposition can lead to release of irritating gases and vapors. Water runoff can cause environmental damage.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

Advice for firefighters**Special protective equipment for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak.

Advice for non-emergency personnel

Material can create slippery conditions.

Advice for emergency responders For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills. After cleaning, flush away traces with water.

Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Recommended Shelf Life

No information available.

Incompatible materials

Strong oxidizing agents, Strong acids, Strong bases

Specific end uses

Specific use(s) Rust Preventative

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	AIHA WEEL
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) -	5 mg/m ³ as mist	5 mg/m ³ as mist		
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) -	5 mg/m ³ as mist	5 mg/m ³ as mist		
Highly refined base oil (Viscosity >20.5 cSt @40°C) -	5 mg/m ³ as mist	5 mg/m ³ as mist		
Stoddard solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³	

8052-41-3		TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³	
2,6-Di-tert-butyl-p-cresol 128-37-0	TWA: 2 mg/m ³ inhalable fraction and vapor	(vacated) TWA: 10 mg/m ³	TWA: 10 mg/m ³	

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Hydrocarbon solvent vapor mixtures which do not have substance specific occupational exposure limits may be evaluated by the Reciprocal Calculation Procedure (RCP) which assigns a recommended occupational exposure limit based on the mass composition and hydrocarbon group guidance values (GGVs). Applicable recommended occupational exposure limits are shown in the table below.

Chemical name	RCP OEL	Manufacturer
Paraffin oils 8012-95-1		TWA: 5 mg/m ³ excluding metal working fluids, highly & severely refined

Chemical name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle 64742-46-7	RCP: TWA 1200 mg/m ³ 143ppm	

Chemical name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle 64742-46-7	RCP: TWA 1200 mg/m ³ 143ppm	
Distillates (petroleum), hydrotreated light 64742-47-8	RCP: TWA 1200 mg/m ³ 182ppm	
Naphtha (petroleum), hydrotreated heavy 64742-48-9	RCP: TWA 1000 mg/m ³	
C12-C14 isoalkanes 68551-19-9	RCP: TWA 1200 mg/m ³	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 600 mg/m ³	
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 150ppm TWA: 1200 mg/m ³	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOT AVAILABLE	TWA: 171 ppm TWA: 1200 mg/m ³	
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 165 ppm TWA: 1200 mg/m ³	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP: TWA 1200 mg/m ³ 182ppm	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	
Hydrocarbons, C13-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	CEFIC-HSPA: 1200 mg/m ³

Exposure controls**Engineering Measures**

Showers
Eyewash stations

Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Tightly fitting safety goggles.
Skin and body protection	Wear protective gloves/clothing.
Respiratory protection	No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Hygiene measures	Regular cleaning of equipment, work area and clothing is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Appearance	clear amber
Odor	No information available	Odor threshold	Not applicable

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	> 140 °C / > 284 °F	Cleveland Open Cup (COC)
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	~ 0.9	g/cm3 @15.5°C
Solubility(ies)	Insoluble in water	
Partition coefficient	Not applicable	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	> 17 cSt @ 40 °C	ASTM D 445
Explosive properties	Not applicable	
Oxidizing Properties	Not applicable	

Other Information

Viscosity, kinematic (100°C)	No information available	
Pour Point	No information available	
VOC Content (ASTM E-1868-10)	103 g/L	ASTM E1868-10
VOC content	No information available	

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None under normal use conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None under normal use conditions

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition

Incompatible materials

Strong oxidizing agents, Strong acids, Strong bases

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Product Information	May be harmful if swallowed and enters airways
Inhalation	Risk of serious damage to the lungs (by aspiration)
Eye contact	Irritating to eyes.
Skin contact	Based on available data, the classification criteria are not met
Ingestion	Risk of product entering the lungs on vomiting after ingestion

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
Highly refined base oil (Viscosity >20.5 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts (TSCA Inventory - CAS# 148520-82-5) 68411-30-3	= 404 mg/kg (Rat)		
2,6-Di-tert-butyl-p-cresol 128-37-0	5000 mg/kg (Rat)	5000 mg/kg (Rabbit)	

Information on toxicological effects

Symptoms May be fatal if swallowed and enters airways. Moderately irritating to the eyes. Prolonged skin contact may defat the skin and produce dermatitis.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
2,6-Di-tert-butyl-p-cresol 128-37-0		Group 3		

*IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans*

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure) Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure) Causes damage to organs through prolonged or repeated exposure if inhaled. Causes damage to organs through prolonged or repeated exposure if swallowed. Causes damage to organs through prolonged or repeated exposure in contact with skin. Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Risk of serious damage to the lungs (by aspiration).

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

No special environmental measures are necessary

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts (TSCA Inventory - CAS# 148520-82-5)	9: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 11: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50	3.4: 96 h <i>Pimephales promelas</i> mg/L LC50		
2,6-Di-tert-butyl-p-cresol	6: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 0.42: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	5: 48 h <i>Oryzias latipes</i> mg/L LC50		

Persistence and degradability The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

Bioaccumulation No information available

Chemical name	Partition coefficient
2,6-Di-tert-butyl-p-cresol 128-37-0	4.17

Mobility The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility.

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

IATA Not regulated

IMDG Not regulated

SECTION 15: REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Complies
KECL	Complies
IECSC	Complies
ENCS	Does not Comply
TCSI	Does not Comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
AICS - Australian Inventory of Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
ENCS - Japan Existing and New Chemical Substances
TCSI - Taiwan National Existing Chemical Inventory

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this regulation, Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

SCAQMD Rule 1144

The sale or distribution in the SCAQM District of California for metal working fluids or direct-contact lubricants is allowed if EITHER the VOC of the product itself OR the VOC of the diluted product at the point of use is less than the following limits: (1) 75 g VOC/L for metal forming, metal removal, metal treating; (2) 50 g VOC/L for metal protection, direct-contact lubricant. The VOC of this product as sold is: 103 g/L gVOC/L (ASTM E-1868-10)

California Proposition 65

This product does not contain any Proposition 65 chemicals.

International Regulations**Ozone-depleting substances (ODS)**

Not applicable

Persistent Organic Pollutants

Not applicable

Chemicals Subject to Prior Informed Consent (PIC)

Not applicable

Other Information

Not applicable

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers REACH registration numbers:

Chemical name	CAS No
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	101316-72-7
Lubricating oils (petroleum), used, noncatalytically refined	101316-73-8
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Residual oils (petroleum), solvent-refined	64742-01-4
Extracts (petroleum), residual oil solvent	64742-10-5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
Paraffin oils	8012-95-1
White mineral oil (petroleum)	8042-47-5

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
Distillates (petroleum), straight-run middle	64741-44-2
Distillates (petroleum), heavy hydrocracked	64741-76-0
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
White mineral oil (petroleum)	8042-47-5
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE

The highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
Distillates (petroleum), hydrotreated middle	64742-46-7
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Naphtha (petroleum), hydrotreated heavy	64742-48-9
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9
C12-C14 isoalkanes	68551-19-9
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9
Alkanes, C14-16	90622-46-1
Alkanes, C12-26-branched and linear	90622-53-0
Alkanes, C11-15-iso-	90622-58-5
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C14, n-alkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C14-C18, n-alkanes, cyclics, aromatics (2-30%)	NOT AVAILABLE
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C16, isoalkanes, cyclics, < 2% aromatics	NOT AVAILABLE
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics	NOT AVAILABLE

SECTION 16: OTHER INFORMATION

NFPA Health hazards 3 Flammability 1 Instability 0 Physical and chemical properties -

Key or legend to abbreviations and acronyms used in the safety data sheet

STOT SE - Specific target organ systemic toxicity (Single exposure)
 STOT RE - Specific target organ systemic toxicity (repeated exposure)
 TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 VOC - Volatile organic compounds
 NIOSH IDLH: Immediately Dangerous to Life or Health

Revision Date 07-21-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet